



## MAJOR PARAFUSOS

### BARRAS REDONDAS - BITOLA E PESO

Bitola D (pol)	Bitola D(mm)	Peso linear (kg/m)	Bitola D (pol)	Bitola D(mm)	Peso linear (kg/m)
Diameter D (in)	Diameter D (in)	Linear Weight (kg/m)	Diameter D (in)	Diameter D (in)	Linear Weight (kg/m)
1/4.	6,35	0,25	1.13/16	46,04	13,06
5/16.	7,94	0,39	1.7/8	47,63	13,98
3/8.	9,53	0,56	2	50,80	15,91
1/2.	12,70	0,99	2.1/16	52,39	16,92
9/16.	14,29	1,26	2.1/8	53,98	17,96
5/8.	15,88	1,56	2.1/4	57,15	20,14
11/16.	17,46	1,88	2.3/8	60,33	22,43
3/4.	19,05	2,24	2.7/16	61,91	23,63
7/8.	22,23	3,05	2.1/2	63,50	24,86
1	25,40	3,98	2.9/16	65,08	26,11
1.1/16	17,46	1,88	2.5/8	66,68	27,40
1.1/8	28,58	5,04	2.3/4	69,85	30,08
1.3/16	30,16	5,60	2.7/8	73,03	32,87
1.1/4	31,75	6,22	3	76,20	35,79
1.5/16	33,34	6,85	3.1/16	77,79	37,30
1.3/8	34,93	7,52	3.1/8	79,38	38,84
1.7/16	36,51	8,22	3.1/4	82,55	42,01
1.1/2	38,10	8,95	3.1/2	88,90	48,73
1.9/16	39,69	9,71	3.3/4	95,35	55,94
1.5/8	41,28	10,50	4	101,6	63,64
1.11/16	42,86	11,32	4.1/16	103,19	65,65
1.3/4	44,45	12,18			

Barras com seção transversal circular, produzidas segundo norma ASTM A36 (aço com baixo teor de carbono) e a norma SAE, 1020 e 1045.  
Round bar (circular transversal section) manufactures as ASTM A 36) low carbon steel, and SAE Std 1020 and 1045  
Fonte (Source) - Gerdau ([www.gerdau.com.br](http://www.gerdau.com.br))

